

**Zip Hydrotap Domestic Boiling, Chilled, filtered
And Sparkling with Chrome tap**

**Boiling and chilled
filtered water, instantly.
Sparkling, too!
Residential model – saving
time, money and energy at
home.**



Simple to install at any sink



New Free-Flow™ feature is great for filling a number of personal water bottles at one time as cold filtered water continues to be available even when rates chilled water capacity is exceeded.



Can be installed away from any sink with the optional Zip 'font' accessory.

Zip HydroTap now offers you sparkling chilled filtered water as well as boiling and chilled filtered water – instantly.

Simple to operate, and with more safety features than ever

- Press the red lever and 'safety' button together to access boiling water.
- Press the blue lever to fill a glass, jug or bottle with chilled filtered water.
- Press both red and blue levers together for sparkling chilled filtered water.
- Life either lever to run water for any pre-set period of 5 to 15 seconds.
- Boiling water can be isolated, if needed, during periods your HydroTap is unattended.

Smarter technology cuts power consumption dramatically

- Power-Pulse™ controls power phasing to cut power costs.
- Set sleep mode to lower boiling water temperature to 65 °C after 2 hours of non-use.
- Set hibernation mode to turn off power totally after 2 hours of non-use.
- Set 24/7 on/off weekly timer to save energy when HydroTap is not in use.

Supplied with submicron water filtration for crystal-clear great-tasting water

- Filters out chlorine, lead, rust. Asbestos fibres and volatile organic compounds.
- Removes impurities larger than one five-thousandth of a millimetre, including the protozoan cysts Cryptosporidium and Giardia. Does not remove fluoride.
- Tested and certified by NSF International to NSF/ANSI standards 42 and 53.



Zip HydroTap® Residential Sparkling
 Boiling and chilled filtered water, instantly. Sparkling, too!
Residential model – saving time, money and energy at home.

Product Code	Boiling Water	Chilled Water	Sparkling Water	Boiling Cap. (litres)	Total Rating @ 230V	Delivery Temp Boiling chilled/Sparkling	Flow Rate ltr/mi Boiling/chilled Sparkling	Gas Press.	Undersink W X D X H
DOMBCS	YES	YES	YES	2.0	1.64kW	98 °C 3 – 6°C	4.0 1.2 – 1.8	2.7 bar	385 412 348

* Not under Free Flow conditions

Location

The tap must be installed to dispense into a suitable sink, or on the optional Tap Font Kit and, if possible Be situated directly above the operational unit, maximum 1 metre away. The operational unit must have a minimum clearance of 50mm left and right, 220mm above and 65mm rear. Cupboard doors should be offset using 4mm buffers provided.

Plumbing

To be installed in accordance with the fitting instructions and UK Water Regulations. Water supply must be potable (drinkable) with a minimum pressure of 1.4 bar. If pressure exceeds 7 bar a pressure limiting valve must be fitted. An isolating valve should be installed between the mains supply and the system.

Carbon Dioxide

The CO2 gas cylinder supplied must be secured in a suitable location using the strap provided. Gas regulator supplied must be fitted. Each cylinder contains 1kg of CO2 and should be installed in a well ventilated room or if it is an enclosed space in an area no less than 38m³

Electrical

Should be installed by a competent person in accordance with the fitting instructions supplied and the UK Electrical Regulations. To be connected to a 13 amp power supply.

Caution

In hard water areas where mineral scale accumulation is an issue consideration should be given to the maintenance required. We recommend the use of the Zip Professional Range of scale filtration systems.

Accessories

- ZT004 – Tap Font Kit
- ZT400 – Twin pack CO2 cylinders
- ZT002 – Submicron replacement filter
- SP91287 – Ventilation Kit

Warranty

2 year on site parts and labour, subject to registration. Zip HydroTap for the home products are designed specifically for use in domestic environments. Use of this product in commercial applications will invalidate the warranty. For full details visit www.zipindustries.co.uk

Technical Support

Contact Zip on Tel: 0800 077 8302

